

Kenmare Moma Processing (Mauritius) Limited

Company R.E.L No. 100018098 Company NUIT No. 40099812

c/o DTOS Ltd, $\mathbf{4}^{\text{th}}$ Floor, IBL House, Caudan, Port Louis, Mauritius Chatham House, Chatham Street, Dublin 2, Ireland.

Rua de Chuindi, No. 67, R/C, Maputo, Mozambique.

Website: www.kenmareresources.com

Tel: +353 1 671 0411 Fax: +353 1 671 0810 Tel: +258 21 499 701 Fax: +258 21 499 731

Email: info@kenmareresources.com

MATERIAL SAFETY DATA SHEET (MSDS) MONAZITE SAND

IDENTIFICATION & COMPOSITION

Product Name Chemical Formula : Monazite Sand : (La,Ce,Nd, Th)PO₄

EINECS No.

Dangerous Goods Class and Subsidiary Risk : None allocated : None Allocated : None Allocated

Hazchem Code Poisons Schedule Uses

: None Allocated : TV and Computer screens

Toner for pottery glaze Manufacturing of Fluorescent

Physical Description/Properties

Appearance (Dry)

: Variable green, yellow, brown free

flowing sand. Odourless and

tasteless.

Vapour Pressure

: Not applicable : 4.6 - 5.7

Specific Gravity

Flashpoint Flammability : Not applicable : Not applicable

Solubility in Water

: Insoluble

Ingredients	CAS Number	Weight %
9		

Rear Earth Oxides

Quartz Zircon

Kyanite

14808-60-7

103170-28-1 149040-68-2

55-60% up to 1%

10-40% 4-8%

Chemical Analysis

Circinical Analysis	
Chemical Name	Typical Weight
ZrO ₂ + HfO ₂	5-35%
P ₂ O ₅	10-30%
SiO ₂	5-20%
Al ₂ O ₃	2-5%
TiO ₂	0-1%
Fe as Fe ₂ O ₃	0-2%
U+Th	0.1-5%
Rear Earth Oxides (La,Nd,Pr, Gd, Dy, Ce, Sm)	20-40%



Kenmare Moma Processing (Mauritius) Limited

Company R.E.L No. 100018098 Company NUIT No. 40099812

c/o DTOS Ltd, 4th Floor, IBL House, Caudan, Port Louis, Mauritius

Chatham House, Chatham Street, Dublin 2, Ireland. Rua de Chuindi, No. 67, R/C, Maputo, Mozambique.

Website: www.kenmareresources.com

Tel: +353 1 671 0411 Fax: +353 1 671 0810 Tel: +258 21 499 701 Fax: +258 21 499 731

Email: info@kenmareresources.com

MATERIAL SAFETY DATA SHEET (MSDS) MONAZITE SAND

Health Effects

Acute:

Swallowed

Non-toxic. There are no known hazards resulting from accidental ingestion as may occur during normal handling. Swallowing a large amount may cause irritation to the digestive system due to abrasiveness.

Eye

Solid and dust can be moderately irritating due to abrasiveness.

Skin

Low hazard.

Inhaled

Normally regarded as general nuisance dust, but can be irritating if inhaled at high concentration.

First Aid

<u>Swallowed:</u> First aid is unlikely to be required, but if necessary wash mouth out with water ensuring the mouthwash is not swallowed. Seek medical attention as a precaution if discomfort occurs.

<u>Eye:</u> Hold eyelid open and flush with plenty of clean water. Continue for at least 15 minutes or until grit is removed. Seek medical attention if soreness or irritation persists.

<u>Skin:</u> Gently remove contaminated clothing to avoid generating dust. Wash material from the skin. If repeated contact results in skin irritation, seek medical advice. Launder clothing before re-use.

<u>Inhaled:</u> Move to fresh air. Blow nose to remove particulates from nasal passages. If any adverse reaction develops, seek medical attention.

First Aid Facilities: Eye wash facilities

Advice to Doctor Treat symptomatically

Radiation: In common with many minerals, Monazite contains low to moderate levels of naturally occurring radioactive elements of the uranium and thorium series. The main radiological hazard from the product is internal exposure to alpha particles given off by inhaled dust. Monazite can be highly radioactive if it contains high levels of thorium. Special precautions should be taken when handling radio active materials.

Precautions for use

Exposure Standards: Inhalable general nuisance dust TWA – 10mg/m₃ (Occupational)

Respirable free silica TWA - 0.2mg/m³

Radiation (combined alpha and gamma) exposure should be as low as reasonably achievable, (ALARA), but should not exceed a total of 100 milli-seiverts over 5 consecutive years.

<u>Engineering Controls:</u> Ventilation requirements will depend on handling methods and the amount in use, but should be sufficient maintain dust levels below exposure limits. Points of dust generation such as conveyor and hopper discharges should be equipped with an effective extraction system.

<u>Personal Protection:</u> Safety glasses or goggles. If risk of inhaling dust is present, wear at minimum, an approved P1 respirator (disposable or cartridge type)

Flammability: Not applicable

SAFETY HANDLING INFORMATION

Transport may be regulated in some countries. Not classified as radioactive pursuant to paragraph 107 of IAEA TS-R-1 regulations. Trucks however should be covered when transporting dry bulk product to prevent dust creation. Storage areas should be ventilated and dust generation minimised when handling.

<u>Spills and Disposal</u>: Wear safety equipment as for normal handling. Avoid generating dust. Vacuum up if possible, otherwise sweep up and re-cycle. If the spilled product is not suitable for re-use, damp down, collect and where possible return to manufacturer for re-processing.

Otherwise dispose of to an approved landfill site and cover with clean fill.

Fire/Explosion Hazard: Not applicable

Other Information:

The material is unlikely to cause any environmental damage. It is insoluble in water and is unlikely to contaminate waterways or food chains.

Additional Contact Points

Emergency Number (24hours): +258 26725055