

PRODUCT NAME: P-10 GAS MIXTURE

1. Chemical Product and Company Identification

BOC Gases, **Division of** The BOC Group, Inc. **575 Mountain Avenue** Murray Hill, NJ 07974

TELEPHONE NUMBER: (908) 464-8100 24-HOUR EMERGENCY TELEPHONE NUMBER: CHEMTREC (800) 424-9300

BOC Gases Division of **BOC Canada Limited** 5975 Falbourne Street, Unit 2 Mississauga, Ontario L5R 3W6

TELEPHONE NUMBER: (905) 501-1700 24-HOUR EMERGENCY TELEPHONE NUMBER: (905) 501-0802 EMERGENCY RESPONSE PLAN NO: 20101

PRODUCT NAME: P-10 GAS MIXTURE CHEMICAL NAME: Methane in Argon COMMON NAMES/SYNONYMS: 10% Methane in Argon, P-10 TDG (Canada) CLASSIFICATION: 2.2 WHMIS CLASSIFICATION: A

PREPARED BY: Loss Control (908)464-8100/(905)501-1700 PREPARATION DATE: 6/1/95 **REVIEW DATES: 6/7/96**

2. Composition, Information on Ingredients

INGREDIENT	% VOLUME	PEL-OSHA ¹	TLV-ACGIH ²	LD ₅₀ or LC ₅₀ Route/Species
Methane FORMULA: CH4 CAS: 74-82-8 RTECS #: PA1490000	10.0	Simple Asphyxiant	Simple Asphyxiant	Not Available
Argon FORMULA: Ar CAS: 7440-37-1 RTECS #: CF2300000	90.0	Simple Asphyxiant	Simple Asphyxiant	Not Available

¹ As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

² As stated in the ACGIH 1994-95 Threshold Limit Values for Chemical Substances and Physical Agents

3. Hazards Identification

EMERGENCY OVERVIEW

Simple Asphyxiant - This product does not contain oxygen and may cause asphyxia if released in a confined area. Maintain oxygen levels above 19.5%. Slightly flammable.

ROUTE OF ENTRY:

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
Yes	No	Yes	Yes	No

PRODUCT NAME: P-10 GAS MIXTURE

HEALTH EFFECTS:

Exposure Limits	Irritant	Sensitization
No	No	No
Teratogen	Reproductive Hazard	Mutagen
No	No	No
Synergistic Effects		
None reported		

Carcinogenicity: -- NTP: No IARC: No OSHA: No

EYE EFFECTS:

None anticipated as product is a gas at room temperature.

SKIN EFFECTS:

None anticipated.

INGESTION EFFECTS:

None known. Ingestion is unlikely as product is gas at room temperature.

INHALATION EFFECTS:

Product is a non-toxic simple asphyxiant. High concentrations may exclude an adequate supply of oxygen to the lungs. Effects of oxygen deficiency resulting from simple asphyxiants may include: rapid breathing, diminished mental alertness, impaired muscular coordination, faulty judgement, depression of all sensations, emotional instability, and fatigue. As asphyxiation progresses, nausea, vomiting, prostration, and loss of consciousness may result, eventually leading to convulsions, coma, and death.

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

NFPA HAZARD CODES

HMIS HAZARD CODES

0

0

Health:

Flammability: 1

Reactivity:

RATINGS SYSTEM

0 = No Hazard 1 = Slight Hazard 2 = Moderate Hazard 3 = Serious Hazard 4 = Severe Hazard

Health:0Flammability:1Reactivity:0

4. First Aid Measures

EYES: None required.

SKIN: None required.

INGESTION:

None required. **INHALATION:**

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area, and if breathing has stopped,

PRODUCT NAME: P-10 GAS MIXTURE

administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

5. Fire Fighting Measures

Conditions of Flammability: Slightly flammable				
Flash point:	Method:		Autoignition	
Not Available	Not Applicable		Temperature: Not Available	
LEL(%): 5		UEL(%): 15		
Hazardous combustion products: None				
Sensitivity to mechanical shock: None				
Sensitivity to static discharge: None				

FIRE AND EXPLOSION HAZARDS:

This mixture may ignite but has a very narrow explosive range and is considered only slight fire hazard.

EXTINGUISHING MEDIA:

None required. Use as appropriate for surrounding materials.

6. Accidental Release Measures

Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in container or container valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest BOC location.

7. Handling and Storage

Electrical classification:

Non-hazardous.

This gas mixture is noncorrosive and may be used with all common structural materials.

Use only in well-ventilated areas. Valve protection caps must remain in place unless container is secured with valve protection outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time.

For additional recommendations, consult Compressed Gas Association Pamphlets P-1, P-14, P-9, and Safety Bulletin SB-2.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

8. Exposure Controls, Personal Protection

EXPOSURE LIMITS¹:

INGREDIENT	% VOLUME	PEL-OSHA ²	TLV-ACGIH ³	LD ₅₀ or LC ₅₀ Route/Species
Methane FORMULA: CH4 CAS: 74-82-8 RTECS #: PA1490000	10.0	Simple Asphyxiant	Simple Asphyxiant	Not Available
Argon FORMULA: Ar CAS: 7440-37-1 RTECS #: CF2300000	90.0	Simple Asphyxiant	Simple Asphyxiant	Not Available

¹ Refer to individual state of provincial regulations, as applicable, for limits which may be more stringent than

those listed here.

² As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)
³ As stated in the ACGIH 1994-1995 Threshold Limit Values for Chemical Substances and Physical Agents.

ENGINEERING CONTROLS:

Local exhaust to prevent accumulation of high concentrations so as to reduce the oxygen level in the air to less than 19.5%.

EYE/FACE PROTECTION:

Safety goggles or glasses as appropriate for the job.

SKIN PROTECTION:

Protective gloves of material appropriate for the job.

RESPIRATORY PROTECTION:

Positive pressure air line with full-face mask and escape bottle or self-contained breathing apparatus should be available for emergency use.

OTHER/GENERAL PROTECTION:

Safety shoes or other footwear as appropriate for the job.

9. Physical and Chemical Properties

PARAMETER	VALUE	UNITS	
Physical state (gas, liquid, solid)	: Gas		
Vapor pressure	: Not Available		
Vapor density at 70 °F (Air = 1)	: ~1.25		
Evaporation point	: Not Available		
Boiling point : Not Available			
	: Not Available		
Freezing point	: Not Available		
	: Not Available		
pH	: Not Applicable		
Specific gravity	gravity : Not Available		
Oil/water partition coefficient	efficient : Not Available		
Solubility (H20)	: Negligible		
Odor threshold	: Not Applicable		
Odor and appearance : Colorless, odorless gas			

10. Stability and Reactivity

STABILITY:

Stable

INCOMPATIBLE MATERIALS: None

HAZARDOUS POLYMERIZATION: Does not occur.

11. Toxicological Information

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

No data given in the Registry of Toxic Effects of Chemical Substances (RTECS) or Sax, Dangerous Properties of Industrial Materials, 7th ed.

12. Ecological Information

No data given.

13. Disposal Considerations

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to BOC Gases or authorized distributor for proper disposal.

14. Transport Information

PARAMETER	United States DOT	Canada TDG
PROPER SHIPPING NAME:	Compressed gases, n.o.s. (methane in argon)	Compressed gases, n.o.s. (methane in argon)
HAZARD CLASS:	2.2	2.2
IDENTIFICATION NUMBER:	UN 1956	UN 1956
SHIPPING LABEL:	NONFLAMMABLE GAS	NONFLAMMABLE GAS

Note: Because of its very narrow explosive range, this gas mixture is considered nonflammable by the DOT.

15. Regulatory Information

Methane is listed under the accident prevention provisions of section 112(r) of the Clean Air Act (CAA) with a threshold quantity (TQ) of 10,000 pounds.

SARA TITLE III NOTIFICATIONS AND INFORMATION

SARA TITLE III - HAZARD CLASSES:

Sudden Release of Pressure Hazard

16. Other Information

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).