

Date of issue: 15 April 2006

MATERIAL SAFETY DATA SHEET

Hazardous according to criteria of Worksafe Australia.

COMPANY DETAILS

COMPANY: Central Chemical Consulting Pty Ltd
ABN: 21 009 431 494

ADDRESS: PO Box 2546, Malaga, Western Australia 6944

INFORMATION

TELEPHONE NUMBER: 61 8 9248 2739

EMERGENCY TELEPHONE NO: 61 8 9248 2739 or 61 8 9246 1102 (out of hours)

FACSIMILE NUMBER: 61 8 9248 2749

IDENTIFICATION

Product Name: LST Heavy Liquid.

Description: Solution of lithium heteropolytungstates in water.

Manufacturers Code: Not applicable.

UN Number: No UN Number allocated.

Dangerous Goods Class and Subsidiary Risk: Not a dangerous good.

Hazchem Code: None allocated.

Poisons Schedule: Not scheduled.

Use: Heavy liquid for density separation of minerals and ores.

LST HEAVY LIQUID

Page 3 of 4

FIRST AID:

- Swallowed:* If swallowed and feeling unwell contact Doctor or Poisons Information Centre.
- Eye:* If in eye rinse out with running water for at least 15 minutes. Contact a doctor immediately.
- Skin:* If on skin wash off immediately with water.
- Advice to Doctor:** Treat Symptomatically.

PRECAUTIONS FOR USE

- Exposure Limits:** No exposure standards have been established for this substance by Worksafe Australia.
- Engineering Controls:** The substance should be used in systems which recover and recycle LST Heavy Liquid.
- Personal Protection:**
- Skin:* Impermeable rubber, vinyl or nitrile gloves should be worn when handling the material.
- Eyes:* Safety glasses/goggles must be worn when handling LST Heavy Liquid or its solids.
- Respiratory:* Not likely to be a route of exposure. Immediately clean up spills to prevent accumulation of dust from dried LST Heavy Liquid.
- Ingestion:* Do not allow eating, drinking or smoking in areas where LST Heavy Liquid is to be stored or used.
- Flammability:** Not flammable.